


Type n° T-BP610 LOW PROFILE ANTENNA UHF / GPS


SPECIFICATIONS

Material:	
Base:	Aluminium alloy EN AW-6082
Radome:	Polycarbonate
Net weight (g):	1000
Dimensions (mm):	106*160
Temperature (°C):	-40° - +80°
Mounting:	According to FEDERTRASPORTI 00104/5



TECHNICAL DATA 400÷470 MHZ:

Frequency range:	400 ÷ 470 MHz
Impedance (Ohms):	50
Max power (W):	200
V.S.W.R.:	less than 1.5
Polarization:	Vertical
Emission:	Omnidirectional
Gain:	2.14 dBi over 1/4 l
Connector:	N Female
DC GROUNDED LIGHTNING PROTECTION	



TECHNICAL DATA GPS:

Antenna type:	Active Planar Patch Antenna
Center frequency:	1575,42 MHz
Bandwidth:	± 1,023 MHz
V.S.W.R:	less than 2.0
Impedance (Ohms):	50
Polarization:	RHCP
Supply voltage:	2.7 ÷ 5 V
Current absorption:	12 ± 1 mA at 2.7 V. 26 ± 1 mA at 5.0 V.
Gain amplifier:	24 ± 1 dB at 2.7 V. 26 ± 1 dB at 5.0 V.
Gain patch antenna:	2 dB
Noise figure:	1.7 ÷ 2.1 dB
Temperature (°C):	-30° - + 80°
Cable:	RG 174 mm.300±10 with FAKRA; capacity: 100pF/m