LOW PROFILE ANTENNA UHF / GPS –GNSS-GALILEO/ W-LAN

T-BP600

SPECIFICATIONS

Material	
Base	Aluminium alloy EN AW-6082
Radome	Polycarbonate
weight (g)	1000
Dimensions (mm)	106*160
Temperature (°C)	-40° - +80°
Mounting	According to FEDERTRASPORTI 00104/5







TECHNICAL DATA 400÷470 MHZ:

Frequency range:	400 ÷ 470 MHz
Impedance (Ohms):	50
Max power (W):	200
V.S.W.R.:	less than 1.6
Polarization:	Vertical
Emission:	Omnidirectional
Gain:	2.14 dBi over 1/4 l
Connector:	N Female

DC GROUNDED LIGHTNING PROTECTION

TECHNICAL DATA GPS/GNSS/GALILEO:

Antenna type:	Active Planar Patch Antenna
Center frequency:	1580 MHz
Bandwidth:	± 28 MHz
V.S.W.R:	less than 2.0
Impedance (Ohms):	50
Polarization:	RHCP
Supply voltage:	2.7 ÷ 5.1 V
Current absorption:	10± 1 mA at 2.7 V. 16 ± 1 mA at 5.0 V.
Gain amplifier:	18 ± 1 dB at 2.7 V. 22 ± 1 dB at 5.0 V.
Gain patch antenna:	2 dB
Noise figure:	1.7 ÷ 2.1 dB
Temperature (°C):	-30° - + 80°
Cable:	RG 316 mm.300±10 connector as request

capacity: 100pF/m

TECHNICAL DATAWIRELESS LAN:

Frequency range:	2400÷2485 MHz
V.S.W.R:	less than 2.5
Polarization:	Vertical
Max power (W):	10
Impedance (Ohms):	50
Gain:	2.14 dBi over 1/4 l
Cable:	RG 316 mm.220±10 connector as request

capacity: 100pF/m

Atel-Antennas S.r.l.

Viale Caduti sul Lavoro, 21/A - 15061 Arquata Scrivia (AL) - Italy

Tel. +39 0143 635496 - Fax +39 0143 666423 - Website: www.atel-antennas.eu - Mail: commerciale@atel-antennas.eu - P. IVA 02442250060