

## ANT.28 °152 / 380-430 MHz + DIPLEXER+ FILTRO FM T-AU036

### SPECIFICATIONS:

Material	Polyamide
Cap	Arnitel EP
Gasket	Pibiflex 2564
Rod	Black
Colour	Black
Base dimensions ( mm )	
Length	60
Width	45
Mounting hole ( mm )	
Squared	15*15
Round	Ø 19
Temperature ( °C )	-30° - +80°



### TECHNICAL DATA 152MHz

Antenna type	1/4 λ Mobile Antenna
Frequency range	149 ÷ 155 MHz
Impedance ( Ohms )	50
Max power ( W )	20
V.S.W.R	Less than 2.5
Polarization	Vertical
Cable length antenna	RG 174 mm.330±20
Connector antenna	FME m.
Output cable 152 MHz	RG58 mm.1500 SMA M./ BNC M.
Cable Antenna - diplexer	RG58 mm.3000 FME F./ TNC M.

### TECHNICAL DATA 380/430 MHz

Antenna type	5/8λ Mobile Antenna
Frequency range	380 ÷ 430 MHz
Impedance ( Ohms )	50
Max power ( W )	20
V.S.W.R	Less than 2.5
Polarization	Vertical
Output cable UHF	RG58 mm.2500 BNC M./BNC M.

### TECHNICAL DATA RADIO

Frequency range	75-110 MHz
Max power	20W
Cable diplexer - filter FM	RG58 mm.1000 BNC M./ SMA M.
Output cable FM	75Ohm mm.1500 FME F./ SCREW SYSTEM