

## MOTOCYCLE ANTENNA 410-470 MHz

### T-AT162

#### SPECIFICATIONS:

|                        |               |
|------------------------|---------------|
| Material               |               |
| Cap                    | Polyamide 6   |
| Gasket                 | Pibiflex 4612 |
| Colour                 | Black         |
| Net weight ( g )       | 120           |
| Base dimensions ( mm ) |               |
| Length                 | 64            |
| Width                  | 46            |
| Mounting hole ( mm )   |               |
| Squared                | 15*15         |
| Round                  | Ø 19          |
| Temperature ( °C )     | -30° - +80°   |



#### TECHNICAL DATA UHF

|                    |                          |
|--------------------|--------------------------|
| Antenna type       | Mobile Antenna           |
| Frequency range    | 410 ÷ 470 MHz            |
| Impedance ( Ohms ) | 50                       |
| Max power ( W )    | 20                       |
| V.S.W.R.           | Less than 3              |
| Polarization       | Vertical                 |
| Emission           | Omnidirectional          |
| Gain ( dBi )       | 2.14                     |
| Rod section        | 1                        |
| Rod elevation      | 74°                      |
| Rod lenght ( mm )  | 345 ± 5                  |
| Rod material       | PIbiflex 2564 BlackRod 1 |
| Cable Lenght       | RG58 mm.2500±20          |
| Connector          | TNCmclamp (non cablato)  |

